

Laundromat **Stacked Tumble Dryer** Specifications

Models		HTT30	HTT45
Control Options		Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)		30 (14) x 2	45 (20) x 2
Width – in (mm)		31.5 (800)	34.5 (875)
Depth – in (mm)	Standard	44.6 (1110)	49.5 (1260)
	ProCapture	44.5 (1130)	–
Height – in (mm)		76.3 (1940)	81.3 (2065)
Cylinder Diameter – in (mm)		30.0 (762)	33.0 (838)
Cylinder Depth – in (mm)		26.0 (660)	30.0 (762)
Cylinder Volume – cu ft (liters)		10.6 (300)	14.8 (420)
Reversing Cylinder		Standard	Standard
Door Opening Size – in (mm)		22.6 (574)	26.9 (683)
Heat Input Power	Standard	73,000 x 2 Btu/hr	95,000 x 2 Btu/hr
	ProCapture	68,000 x 2 Btu/hr	–
Gas Connections* – in (mm)		0.5	0.5
Air Outlet – in (mm)	Standard	1 x 8 (200) Oval	1 x 10 (250) Oval
	ProCapture	1 x 8 (200) Oval	–
Motor - HP	Fan	2 x 0.5	2 x 0.5
	Cylinder	2 x 0.5	2 x 0.5
Airflow – cfm (liters/sec)		2 x 400 (380)	2 x 600 (285)
Electrical Specs - amps	(B) 100-120V/50/60/1	16	–
	(X) 200-240V/50/60/1/3	Standard - 9 ProCapture - 10	12 –
	(Q) 200-240V/50/60/3	–	–
Shipping Dimensions Approx. – in (mm)	Width	32.5 (830)	35.5 (900)
	Depth	47.0 (1190)	54.0 (1370)
	Height	79.9 (2030)	84.9 (2160)
Net Weight – lb (kg)	Standard	580 (265)	690 (315)
	ProCapture	620 (280)	–
Shipping Weight – lb (kg)	Standard	615 (280)	735 (335)
	ProCapture	655 (295)	–
Agency Approvals		UL	UL